

Compact peripherals with  
outsized performance.



**OLIVETTI PG L22 AND L22 SPECIAL  
DIGITAL PRINTERS**



**olivetti**

## The new monochrome printers for your business

The PG L22 and PG L22 Special are two new monochrome printers from Olivetti for small workgroups looking for superior performance and configuration flexibility. Extremely reliable and compact, the new models deliver excellent quality on high-resolution photos and text alike, and support a broad range of paper devices.

The Olivetti PG L22 and PG L22 Special guarantee outstanding productivity, thanks to a speed of 22 pages per minute and a 16 MB memory, expandable to 272 MB. A full range of options, including a second 500-sheet paper tray, a universal feed for different types of paper and a selection of Flash memory and RAM expansions, make these printers the best solution for business needs. The optional network card and integrated Web Server enable their use as remotely controlled shared devices.

Additionally, the Olivetti PG L22 Special features a practical LCD display for at-a-glance control of printer status, as well as a high-capacity cartridge toner to keep copy costs down. With the PostScript option, the PG L22 Special is the perfect printer device for even the most demanding user.



**Olivetti PG L22**  
22 ppm monochrome printer

## TECHNICAL SPECIFICATIONS

### General characteristics

Printing method: electrophotographic  
Printing speed: 22 ppm  
Warm-up time: 35 seconds  
Time to first page: 6.2 seconds  
Resolution: 1200 dpi  
Processor: PowerPC at 266 MHz  
Memory:  
- RAM 16 MB standard/272 MB max.  
- Flash 8/16 MB optional

### Emulations

PCL5e, PCL6, Epson FX, IBM Proprinter (optional PostScript3 on the PG L22 Special only)

### Operating systems supported

Windows 95/98/98SE/ME/NT4 Workstation/ NT4 Server/2000/XP Professional/XP Home/ Mac OS X (10.1 or later)/Mac OS 8.6 (or later)  
For the PG L22 Special only: Unix and Linux variants via PPD with PS option

### Network protocols

Ethernet 10/100Base-TX, TCP/IP, Netware, EtherTalk and NetBEUI

### Interfaces

Standard: IEEE1284 bi-directional parallel, USB 2.0  
Optional: Ethernet 10/100BaseTX, RS232C 25-pin serial

### Paper management

Standard tray capacity: 250 sheets, 60-105 g/m<sup>2</sup>  
Paper formats standard tray: A4, A5, B5 (JIS), A6, Letter, Legal 13, Legal 14, Executive  
Manual feeder capacity: 1 sheet, 60-120 g/m<sup>2</sup>  
Optional tray capacity: 500 sheets, 60-105 g/m<sup>2</sup>  
Paper formats optional tray: A4, A5, B5 (JIS), Letter, Legal 13, Legal 14, Executive  
Optional multifeeder capacity: 100 sheets/50 envelopes

Formats optional multifeeder: A4, A5, B5 (JIS), A6, Letter, Legal 13, Legal 14, Executive, Monarch, Com-9, Com-10, DL, C5

Output paper capacity: 150 pages face-down, 50 pages face-up

### Other features

Power supply: 230V CA +/- 10%  
Frequency: 50/60 Hz +/- 2%  
Noise level: < 53 dB(A)

Operating conditions: temperature from 10°C to 32°C, non-condensing humidity from 20 to 80%

Storage temperature: from -10°C to 43°C, non-condensing humidity from 10 to 90%

### Consumption:

- print mode 360 W  
- standby 66 W  
- Power save: 14 W

### Productivity

Up to 30,000 pages/month

### Dimensions (HxWxD) and Weight

PG L22: 200 x 355 x 395 mm, 9 kg

PG L22 Special: 215 x 355 x 395 mm, 9 kg

### Consumables

Toner PG L22: up to 2,500 pages (5% coverage)

Toner PG L22 Special:

- standard capacity toner: up to 2,500 pages (5% coverage)  
- high capacity toner: up to 6,000 pages (5% coverage)

Image unit: up to 25,000 pages continuous printing, up to 17,000 pages at 3 pages per job

[www.olivetti.com](http://www.olivetti.com)

Product performances are referred to an appropriate use under optimal conditions.

With the right to change technical specifications.

The registered trademarks are the property of their respective owners.

**olivetti**

The Olivetti PG L22 and PG L22 Special are distributed by Olivetti Tecnost S.p.A. I/reagrafica (03/05) Code 25023-00